

SuperK EVO

Industrial white light laser



High brightness over a wide spectral bandwidth

Ideal for optical device characterization and Test & Measurement.

The SuperK EVO is a range of cost-efficient white light lasers based on our extremely reliable fiber laser technology. Designed for maintenance-free operation, the lasers are extremely stable, boast a long lifetime, and grant a low cost of ownership.



SuperK EVO

Applications

OCT

Thin film

General illumination

Test & Measurement

Inspection, sorting, and quality control

Replacement of Superluminescent Emitting Diodes (SLEDs, SLDs)

Characterizations of optical components and materials

Ease of use

High brightness

The SuperK EVO has a very high brightness across the 425 - 2400 nm range.

High repetition rate

With a standard repetition rate of 20 or 30MHz, the EVO is perfectly suited for Test & Measurement and optical device characterization.

Graphical user interface and software development kit

The SuperK EVO is compatible with all existing SuperK filters and accessories.


Get an utmost user-friendly operation through our NKT Photonics CONTROL software or a direct interface through the free software development kit.

SuperK EVO

NKT Photonics CONTROL

Like other NKT Photonics lasers, the SuperK EVO can be controlled by our intuitive CONTROL software that gives easy access to all laser functions. The software automatically detects all units attached to the computer.

You can control the source and any filtering accessories from CONTROL. It is easy to use and supports touch input as well as traditional mouse+keybord control.



Benefits

- Versatile cost-efficient white light laser platform
- High brightness
- High repetition rate
- Robust and compact industrial design
- Free software development kit
- Plug and Play with all SuperK accessories
- Maintenance-free 24/7 operation
- Simple and intuitive user interface via NKT Photonics CONTROL



Repetition rate (fixed)	20, 30 MHz
Trigger out signals	NIM
Trigger signal jitter	< 20 ps
Adjustable trigger delay ¹	Up to 9.2 ns
Adjustable trigger delay resolution	15 ps

¹The electrical output trigger signal can be delayed up to 9.2 ns in steps of 15 ps.w

SuperK EVO

Support and warranty

Before shipping, all our SuperK lasers undergo an extensive burn-in to ensure performance and conformity to specifications. Our systems boast over 10,000 hours of continuous lifetime and underlines the high reliability of our NKT Photonics Crystal Fiber technology.


Lifetime and service

The all-fiber architecture ensures a stable 24/7 operation and a maintenance-free lifetime of thousands of hours.Intended for industrial use, its rugged and compact design make it easy to mount and handle.


Performance

SuperK
EVO

Spectral radiance



Spectral power density



Specifications

SuperK EVO

Optical

Model	ERL - 04	EUL - 10
Repetition rate [MHz]	20	30
Spectral coverage [nm]	510 - 2000	425 - 2250
Spectral power density [mW/nm]	N.A.	0.08 @ 450 nm
	0.10 @ 532 nm	0.10 @ 532 nm
	0.20 @ 650 nm	0.16 @ 650 nm
	0.25 @ 780 nm	0.20 @ 780 nm
	0.25 @ 800 nm	0.20 @ 800 nm
Total power [W]	≈ 1	≈ 0.3
Visibe power (350-850 nm) [mW]	≈ 40	≈ 60
Total power stability, RMS [%]	± 1	± 1
Cut-in wavelength [nm] ¹	510	425
Polarization	Random	Random

¹ Spectral power density > 0.1 mW/nm

Beam diameter (collimated version) [mm]	≈ 1 @ 532 nm	≈ 1 @ 532 nm
	≈ 2 @ 1100 nm	≈ 2 @ 1100 nm
	≈ 3 @ 2000 nm	≈ 3 @ 2000 nm
Fiber output	Collimated	Collimated
Beam divergence [mrad]	< 1.5	
Laser Class	4	

Specifications

Electrical/Mechanical

Model	ERL - 4	EUL - 10
Output fiber length [m]	1.5	1.5
Computer interface	USB 2.0/RS-232/Ethernet	USB 2.0/RS-232/Ethernet
Sync (trigger) output	NIM	NIM
Power supply requirements [V DC]	24	24
Power consumption [W] ¹	< 30	< 30
Door interlock connector ²	2-pin LEMO	2-pin LEMO
External bus interface	15 D-Sub	15 D-Sub
Operation temperature [°C]	18 - 35	18 - 35
Storage temperature [°C]	-10 - 60	-10 - 60
System cooling ³	Passive	Passive
Dimensions (WxHxL) [mm]	200 x 90 x 325	200 x 90 x 325
Weight [kg]	6	6

¹ Power consumption is depending on the total output power. ² SuperK EVO is a class 4 laser and required to be connected to a door interlock/circuit.³ Heat radiation from the base plate.

SuperK EVO

Software Development Kit (SDK)

The free software development kit (SDK) enables control of the SuperK EVO laser using third party software and hardware.

The SDK contains a full description of the communication protocols as well as LabView drivers and C++/C# source code.


Technical Drawings

SuperK EVO

All NKT Photonics products are produced under our quality management system certified in accordance with the ISO 9001:2015 standard.



© Copyright 2023 NKT Photonics A/S. All Rights Reserved. SuperK EVO_20230201



SOLUTIONS FOR INNOVATORS