

SuperK FIANIUM OCT

Low-noise supercontinuum white light laser



Broadband output and low noise

Ideal for Optical Coherence Tomography

The SuperK FIANIUM OCT series is a supercontinuum source optimized for ultra-high resolution Optical Coherence Tomography and multimodality applications.

The ultra-broad output and low noise makes SuperK supercontinuum lasers ideal OCT sources when micron resolution or a special wavelength range is needed.



SuperK FIANIUM OCT

Applications

Optical Coherence Tomography

White light interferometry

Multimodality OCT applications:

- **Autofluorescence**
- **Spectroscopy**
- **Doppler OCT**

Ease of use

Optimized for ultra-high resolution OCT

The new SuperK FIANIUM OCT series from NKT Photonics is a supercontinuum source optimized for ultra-high resolution OCT and multimodality applications.

The SuperK FIANIUM OCT series have the market's lowest noise. It is optimized for low-noise performance to yield high-contrast, low-noise images in OCT systems.

Combined with a broadband spectrometer, the SuperK FIANIUM OCT can power Optical Coherence Tomography systems down to 1-2 μm axial resolution.


Replaces expensive Ti:Sapphire lasers

Due to its low noise and broadband output, it matches the performance of the bulky and costly Ti:Sapphire lasers.

Model	FIU-6 OCT	FIR-9 OCT
Cut-in wavelength	$\approx 425 \text{ nm}$	$\approx 640 \text{ nm}$
Visible power	$\approx 600 \text{ mW}$	$\approx 900 \text{ mW}$

Features

- Low noise
- Broadband output
- True single-mode output
- Multimodal OCT light source
- Replaces Ti:Sapphire lasers and SLEDs
- Unsurpassed reliability and lifetime
- OCT optimized filter option



SuperK FIANIUM OCT


NKT Photonics CONTROL

Like other NKT Photonics lasers, the SuperK EVO can be controlled by our intuitive CONTROL software that gives easy access to all laser functions. The software automatically detects all units attached to the computer.


You can control the source and any filtering accessories from CONTROL. It is easy to use and supports touch input as well as traditional mouse + keyboard control.

SuperK FIANIUM OCT

Relative Intensity Noise



Typical output Spectrum



Support and warranty

Before shipping, all our SuperK lasers undergo an extensive burn-in to ensure performance and conformity to specifications. Our systems boast over 10,000 hours of continuous lifetime and underlines the high reliability of our NKT Photonics Crystal Fiber technology.

Lifetime and service

The all-fiber architecture ensures a stable 24/7 operation and a maintenance-free lifetime of thousands of hours. Intended for industrial use, its rugged and compact design make it easy to mount and handle.


Collimator

SuperK FIANIUM OCT

The optical output of the laser is a collimator at the end of an armored fiber cable.

A collimated beam exits the collimator from a steel sleeve connector designed for insertion into a receptacle of a target optical device such as, for example, a SuperK accessory, holder, or specifically engineered optical device.

Once inserted, the substantial construction of the collimator maintains the output beam alignment.



Specifications

SuperK FIANIUM OCT

Optical

Model	FIU-6 OCT	FIR-9 OCT
Cut-in wavelength [nm]	< 425	< 640
Visible power (350-850 nm) [mW]	≈ 600	≈ 900
Spectral power density [mW/nm]	0.5 @ 450 nm	N.A
	0.9 @ 532 nm	N.A
	1.2 @ 650 nm	0.6 @ 650 nm
	2.0 @ 780 nm	3.2 @ 780 nm
	1.6 @ 800 nm	3.5 @ 800 nm
Total power [W]	< 6.5	< 6.5
Repetition rate [MHz]	312 ± 3	312 ± 3
Power stability [%]	< ± 0.5	< ± 0.5
Polarization	Random	Random
Beam quality	Diffraction limited	Diffraction limited
Collimated Beam diameter [mm]	≈ 1 @ 530 nm	≈ 1 @ 530 nm
	≈ 2 @ 1100 nm	≈ 2 @ 1100 nm
	≈ 3 @ 2000 nm	≈ 3 @ 2000 nm
Beam pointing accuracy [mrad] ¹		< 1

¹ Measured relative to the mechanical axis running through the center of the collimator.

Specifications

Electrical/Mechanical

Computer interface	USB 2.0/RS-232/Ethernet
Operation voltage [Hz]	100-240 VAC 50/60
Power consumption [W]	< 100
Door interlock connector ¹	2-pin LEMO
External bus interface ²	16-pin sub-D
System cooling	Air-cooled
Length of output fiber [m]	1.5
Operation temperature [°C]	18 - 30
Storage temperature [°C]	-10 - 55
Dimensions (WxHxL) [mm]	440 x 251 x 400
Weight [kg]	18 (19 with pulse picker)

¹ The SuperK FIANIUM OCT is a Class 4 laser and is required to be connected to a door interlock/circuit

² External communication and power supply port for accessories






SuperK FIANIUM OCT

Software Development Kit (SDK)

The free software development kit (SDK) enables control of the SuperK FIANIUM OCT laser using third party software and hardware.

The SDK contains a full description of the communication protocols as well as LabView drivers and C++/C# source code.

Technical Drawings



SuperK FIANIUM OCT

All NKT Photonics products are produced under our quality management system certified in accordance with the ISO 9001:2015 standard.



© Copyright 2022 NKT Photonics AS. All Rights Reserved. SuperK FIANIUM OCT_20220920

SOLUTIONS FOR INNOVATORS